25X
-----

## CENTRAL INTELLIGENCE AGENCY

## INFORMATION REPORT

This Document contains information affecting the National Defense of the United States, within the meaning of Title 18, Sections 793 and 794, of the U.S. Code, as amended. Its transmission or revelation of its contents to or receipt by an unauthorized person is prohibited by law. The reproduction of this form is prohibited.

SECRET/C	CONTROL	HE CONABOTE	CIALS	ONLY
----------	---------	-------------	-------	------

COUNTRY	East Germany	REPORT		25X1
SUBJECT	KVP Decimeter Radio Network	DATE DISTR.	128 June	1954
		NO. OF PAGES	4	,
DATE OF INFO.		REQUIREMENT NO.	RD:	0514
PLACE ACQUIRED		REFERENCES	\	' 25X
	This is UNEVA  THE SOURCE EVALUATIONS IN THIS  THE APPRAISAL OF CONTENT (FOR KEY SEE REV.	I IS TENTATIVE.	· · · · · · · · · · · · · · · · · · ·	
				25X

Frankfurt/Oder Goerlitz Bautzen-Neustadt Hellau Airfield, Dresden Frauenstein Adelsberg, Chemnitz Rochlitz Leipzig

Petersberg (Halle) Effurt

Magdeburg Schwerin Rostock Stralsund greifswald Anklam

Relay stations will be set up between Frankfurt and Goerlitz; Halle and Erfurt, at Kyffhaeuser between Erfurt and Magdeburg and between Magdeburg and Schwerin.

- b. The system is intended to carry speech channels only and is to be used in comfunction with the existing static line network, with which facilities for interconnection will be provided. the Russians would also make use of the decimeter links.
- 25X1 Construction began in April 1953 and completion of the whole system is due some time in 1954. 25X1 25X1 no individual link had been brought into operation.
- 2. a. The buildings are of wood on concrete foundations. The following equipment is installed by Sachsenwerk Radeberg in conjunction with VEB Anlagenbau, Berlin-Koepenick:

SECRET/CONTROL - U.S. OFFICIALS ONLY

## 25 YEAR RE-REVIEW

STATE	х	ARMY	x	NAVY	х	AIR	х	FBI	AEC	ORR	Ev	х	OSI	Ev	x
										 • • •					
(Note: Wa	shingtor	Distribution	n India	ated By "X"	'. Field	Distribution	n By '	·#"\							

## SECRET/CONTROL - U.S. OFFICIALS ONLY

- 2 -

Aerial system (See paragraph 2,d, below)
Transmitter and Receiver Equipment RVG 903 B
Carrier Telephony Equipment EV16
3 KW gasoline engine driven generator with automatic change-over against mains failure
Pintsch automatic voltage regulator

230V. AC mains supply is obtained from a transformer installed near each station. Frequencies will be changed at each relay station in order to avoid mutual interference between transmitters and receivers.

- b. Maintenance will be carried out by Volkspolizei Signals personnel who are being trained at Radeberg and later at the KVP Signals School at Pirna. All stations will be permanently staffed; the most simple type of relay station will require 5 men working shifts, i.e. 2-2-1. Under normal conditions, however, transmissions will only take place during | ILLEGIE For the future, Sachsenwerk-Radeberg is developing an unattended relay station.
- c. Equipment RVG 903B. Designed for operation within the frequency range 1200-15000 mcs. = 20-25 cm. wavelength. Accommodates 10 channels. Transmitter 4-stage frequency modulated comprising one generator state, one mixing amplifier stage and two HF amplifier stages. Transmitter tubes LD-11 and LD-12 with air cooling. Final output 15-20 watts.
- d. Receiver. Resonance oscillator circuit with LD-12 tube. Automatic frequency hunting and volume control on the heterodyne principle. Intermediate frequency = 10.7 mcs. Frequency bandwidth = 30-400 kcs, but only the range 30-440 kcs is used (140 kcs = carrier frequency for level control). The whole equipment is rack-mounted.
- e. The aerial system, consisting either of a horn or parabolic antenna, is on a tower belonging to the inn situated on the highest point of the Schleifberg (known locally as "Czorneboh") near Bautzen. 2 The tower has several storys which house the transmitting and receiving equipment. A wooden structure, similar to a fire tower of four platforms, was erected on top of the tower two years ago to increase the field strength. The antennas were beamed on the Sachsenwerk Radeberg, as an experiment. pair are horn aerials with pre-fixed lenses and polarized horizontally and vertically. They are used in conjunction with the RVg-903B decimeter set and require a separate aerial cable for sending and receiving. The top arir are parabolic aerials of the latest type (sic). They are used for both stationary and mobile decimeter stations. The dipole is arranged vertically  $(\lambda/4)$ . Transmission and reception are carried out over an antenna cable and a high pass filter. The diameter of the reflector is 1.5 meters. The obsolescent horn antenna is no longer being produced, as the disadvantages of the parabolic antenna (small aerial gain) can be offset by an increase in the strength of the emission.
- f. Telephone Carrier Equipment. The EV 16 carrier equipment used in conjunction with the RVG 903B is basically the same as ME8, but is equipped for 16 channels in the range 6-60 kcs. The channel bandwidth is 30-2400 c/s with 2.9 kc. spacing.

3. The following stations were known

25X1

25X1

Location

Valtenberg near Neukirch Height above sea level

609.2 m.

1,06

Ruhner Berge/ Jabelitzer Hoehen, Hohe Burg (also Deutsche Post)

zer Hoehen,

SECRET/CONTROL - U.S. OFFICIALS ONLY

SECRET/CONTROL - U.S. OFFICIALS ONLY

- 3 -

25X1

Location	Height	above	sea	leve
Boxdorf near Dresden (also Deutsche Post)		29	93.5	m.
Halle-Petersberg (Kloster) (also Deutsche Post)			-	
Kyffhaeuser (also Deutsche Post		45	57	m.
Erfurt-Am Anger (also Deutsche Post)		32	28.9	m.
Bad Freienwalde, Platzfelde (also Deutsche Post)		15	52.8	m.
Marienthal Eckartsberga near Bad Sulza			<del>-</del> -	
Rheinsberg Fire Watch Tower		10	00	m.
Chemnitz-Adelsberg (also Deutsche Post)		35	97.6	m.

Berlin-Koepenick Mueggelberg

4. Point to Point systems. The KVP is equipped with portable transmitter/receiver sets, type DT 911-920, operating in the wavelength range 50-60 cm. and with a working distance of 70-80 km. This equipment was also supplied by Sachsenwerk Radeberg and can be used for point to point telephone or telegraph links. They have no connection with the main decimeter system. The Soviet Army and the Seepolizei have also been supplied with several hundred of these sets by Sachsenwerk-Radeberg.

L.	Comment:	See	attached	schematic	diagram.	25 <b>X</b>	1

2. Comment: Because of its central position in the Lusatian mountains, 25X1 the Schleifberg is particularly important from a strategic standpoint.

The East German Ministry of Posts and Telecommunications has no interest in the site, but it may be of interest to the KVP.

SECRET/CONTROL - U.S. OFFICIALS ONLY